

2/9/1

DIALOG(R)File 351:Derwent WPI
(c) 2005 Thomson Derwent. All rts. reserv.

014866404

WPI Acc No: 2002-687110/200274

XRAM Acc No: C02-194280

Thermoplastic elastomer composition, used as molding material for preparation of e.g. automotive and domestic appliance parts, comprises polyisobutylene block-polystyrene block copolymer and polyphenylene ether resin

Patent Assignee: KANEKA CORP (KANF)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 2002226665	A	20020814	JP 200122333	A	20010130	200274 B

Priority Applications (No Type Date): JP 200122333 A 20010130

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 2002226665	A		8 C08L-053/00	

Abstract (Basic): JP 2002226665 A

NOVELTY - A thermoplastic elastomer composition (I) comprises:

(A)

a block copolymer composed of (A1) isobutylene polymer block and

(A2)

an aromatic vinyl polymer block (99-50 wt.%); and (B) polyphenylene ether resin (1-50 wt.%).

USE - The thermoplastic elastomer composition (I) is useful as molding material for preparation of automotive parts, domestic appliance parts, packings, gaskets, medical instruments etc, and is also useful as wire insulating compound, sealing compound, etc.

ADVANTAGE - The thermoplastic elastomer composition (I) has improved permanent set.

pp; 8 DwgNo 0/0

Technology Focus:

TECHNOLOGY FOCUS - POLYMERS - Preferred Copolymer: The block copolymer (A) is composed of (A1) (50-95 wt.%, more preferably 70-95

wt%) and (A2) (50-5 wt.%, more preferably 30-5 wt.%). Preferred (A2) is

(co)polymer of styrene and/or alpha-methylstyrene).

Preferred Properties: The Mw of (A) is 3,000-1,000,000 (preferably

5,000-500,000, and optimally 20,000-100,000).

Preferred Resin: The polyphenylene ether resin (B) is preferably

composed of polyphenylene ether resin (especially poly(2,6-dimethyl-1,4-phenylene) ether resin) (50-100 wt.%) and polystyrene resin (50-0 wt.%).

Preferred Composition: The elastomer composition (I) is prepared by

blending (A), (B) and optional additive(s) (e.g. plasticizer, filler,

stabilizer, flame retardant, etc.) to satisfy

((A2)+(B))/((A)+(B))=10-50 wt.%, and then kneading the mixture.
Title Terms: THERMOPLASTIC; ELASTOMER; COMPOSITION; MOULD; MATERIAL;
PREPARATION; AUTOMOTIVE; DOMESTIC; APPLIANCE; PART; COMPRISE; BLOCK;
POLYSTYRENE; BLOCK; COPOLYMER; POLYPHENYLENE; ETHER; RESIN
Derwent Class: A13; A17; A25
International Patent Class⁴ (Main): C08L-053/00
International Patent Class (Additional): C08L-071-12; C08L-053/00
File Segment: CPI
Manual Codes (CPI/A-N): A04-C01A; A04-G05; A05-H07A; A07-A04E; A11-B01
Polymer Indexing (PS):
<01>
001 018; R00966 G0055 G0044 G0033 G0022 D01 D02 D12 D10 D51 D53 D58
D84
; G0102-R G0022 D01 D12 D10 D18 D51 D53; R00708 G0102 G0022 D01
D02
D12 D10 D19 D18 D31 D51 D53 D58 D76 D88; R00673 G0102 G0022 D01
D02
D12 D10 D19 D18 D31 D51 D53 D58 D76 D89; H0135 H0124; H0011-R;
H0044-R H0011; K9449; P1150 ; P1741
002 018; H0022 H0011; R00966 G0055 G0044 G0033 G0022 D01 D02 D12
D10
D51 D53 D58 D84; R00708 G0102 G0022 D01 D02 D12 D10 D19 D18 D31
D51
D53 D58 D76 D88; H0044-R H0011; H0135 H0124; K9449; P1150 ;
P1741
003 018; H0022 H0011; R00966 G0055 G0044 G0033 G0022 D01 D02 D12
D10
D51 D53 D58 D84; R00673 G0102 G0022 D01 D02 D12 D10 D19 D18 D31
D51
D53 D58 D76 D89; H0044-R H0011; H0135 H0124; K9449; P1150 ;
P1741
004 018; R00966 G0055 G0044 G0033 G0022 D01 D02 D12 D10 D51 D53 D58
D84
; R00708 G0102 G0022 D01 D02 D12 D10 D19 D18 D31 D51 D53 D58
D76
D88; R00673 G0102 G0022 D01 D02 D12 D10 D19 D18 D31 D51 D53 D58
D76
D89; H0135 H0124; H0033 H0011; H0044-R H0011; K9449; P1150 ;
P1741
005 018; ND04; K9745-R; K9449; B9999 B3792 B3747; B9999 B5618
B5572;
Q9999 Q7352 Q7330; Q9999 Q7681-R; Q9999 Q9007; Q9999 Q9018;
Q9999
Q8026 Q7987; Q9999⁴ Q9234 Q9212; Q9999 Q9289 Q9212; B9999 B4171
B4091 B3838 B3747; B9999 B3907 B3838 B3747
006 018; B9999 B5094 B4977 B4740
007 018; A999 A384
008 018; A999 A237
009 018; A999 A486-R
010 018; A999 A248-R
<02>
001 018; D11 D10 D19 D18 D31 D76 D50 D88; P0997 P0964 H0293 F34 D01
D18
; K9449
002 018; R00708 G0102 G0022 D01 D02 D12 D10 D19 D18 D31 D51 D53 D58
D76
D88; H0000; K9449; P1741 ; P1752

003 018; ND04; K9745-R; K9449; B9999 B3792 B3747; B9999 B5618
B5572;
Q9999 Q7352 Q7330; Q9999 Q7681-R; Q9999 Q9007; Q9999 Q9018;
Q9999
Q8026 Q7987; Q9999 Q9234 Q9212; Q9999 Q9289 Q9212; B9999 B4171
B4091 B3838 B3747; B9999 B3907 B3838 B3747
004 018; A999 A384
005 018; A999 A237
006 018; A999 A486-R
007 018; A999 A248-R
?